

Pipe Fitting

Product: FFJ 3001-2

Application	Injection PVC Pipe Fitting
Type	Lead
Content (PbO)	36.5 - 39.5%
Typical Addition	4.0 - 6.0
Lubrication	★★★
Form	Flake

Typical Formulation

Material	PVC Pipe Fitting	
PVC K57	100	
CaCO ₃	5-10	
FFJ 3001-2	4.0-6.0	
ACR Processing Aid	0.5-2.5	
Pigment	As needed	

Properties

FFJ 3001-2 is an onepack stabilizer applied in injection of PVC pipe fittings. It provides excellent processing performance to produce PVC pipe fittings with high impact strength, surface finish and overall heat stability.

FFJ 3001-2 is supplied in low dust flake form which should be mixed in a high speed mixer to a discharge temperature of 120 °C and in low speed mixer to a discharge temperature of 40 °C.

All raw materials and every batch of one pack are tested to a high standard to ensure product consistency and meet the high quality demands of the customer. A quality assurance certificate can be provided for each product batch according to customer's request and supported by our ISO 9001:2008 Quality management system.

Package

3 in 1 plastic/paper bag(25kg N.W) or plastic woven container sack. Period of quacity guarantee is one year.

Storage

Stored in dry place, to avoid high temperature, kept away from sulfide.

NANJING JINLING CHEMICAL CO.,LTD.

Add:No.55, NJC Road, Chemical Industry Park Nanjing China. Post Code: 210047
 Tel: (025) 85315451、84712677、84716016 Fax: (025) 85315451
 Email: angel.cai@njchem.net Web: www.njchem.net